

Wieland-Kessler Copper Press Submittal Package-System Data Sheet

System Description

Using modernized cold press connection technology for a wide assortment of more than 350 fittings, in dimensions ranging from ½" to 4", Wieland-Kessler Press provides safe and economical copper pipe installation systems.

Applications

All tubing must comply with the ASTM B88 standard. Wieland-Kessler Press Fittings are approved for installations in both above and below ground applications, local approval must be obtained prior to such installation for compliance with local code.

Operating Parameters

Operating Pressure 200PSI Max.
Test Pressure 600 PSI Max.
Low Pressure Steam 15PSI Max @ 68°F
Operating Temperature 0°F – 250°F

Approved Applications

Hydronic Heating (w/Glycol)
Chilled Water
Compressed Air (200 PSI Max)
Non-Medical Gases (140 PSI Max)
Low Pressure Steam (15 PSI Max)
Vacuum (24.5" Mercury Max @ 68°F)

System Benefits

Fast and Easy to use
Flameless
Permanent Connections
Wide Capacity from ½" – 4"
Large Selection of Fittings
Consistent Professional Appearance
Less Equipment Required
Environmentally Friendly Connection System
Versatility of Fittings and Tools for a Variety of Applications

Fittings

Wieland-Kessler Press Fittings are offered in 350 plus configurations including: Elbows, Couplings, Reducers, Tees, Reducing Tees, Threaded Adapters, Unions, Caps, Flanges, and Ball Valves. All fittings are wrot copper or maintain a Lead Free brass assembly. All Parts are Lead Free compliant.

Warranty

Wieland-Kessler Press Fittings carry a 50-year warranty against defects in material and workmanship.

*\$1500 = FFA for all fittings & valves / \$750 = FFA for just copper & press fittings
Order before noon EST = ship the same day / Order after noon EST = ship next day
Shipping from 3 regional warehouses – NJ, IL and GA*

*CUSTOMER SERVICE SPECIALISTS – Ask for Kerin or Lisa
konnections@wieland-kessler.com
P 800-526-5104 ext. 3156 / F 888-863-4396*
