

**Product Description:**

Wrot Copper Pressure and DWV fittings for use in plumbing or mechanical applications. Available sizes ranging from ¼” to 8” in diameter, all wrot copper solder joint fittings shall be manufactured in South Korea and qualify under KORUS as domestic equivalent fittings. Product is designed to join ASTM B88 and ASTM B280 Seamless Copper Tube.

**Material:**

Wrot Copper fittings shall be made from material in compliance with ASTM B75 and of UNS C12200 grade of copper.

**Key Specifications:**

Wrot Copper, solder joint, pressure fittings shall conform to the NSF/ANSI 61 Annex G requirements. Wrot copper pressure fittings shall be manufactured to meet ASME B16.22 and MSS SP104. Wrot DWV copper fittings shall be made to meet ASME B16.29. All threaded fittings conform to ASME B1.20.1.

**Installation:**

Installations shall comply with the latest applicable building codes for the local jurisdiction. For detailed installation instructions, consult the Copper Development Association at copper.org.

**References:**

NSF/ANSI 61 Annex G Safe Drinking Water Act (third party certification)

ASTM B75 Seamless Copper Tube

C12200 99.9% pure copper

ASME B16.22 Wrot Copper and Copper Alloy Solder Joint Pressure Fittings

MSS SP104 Wrot Copper Solder and Joint Pressure Fittings

ASME B16.29 Drain, Waste and Vent (DWV) Fittings

ASME B1.20.1 Threaded Fittings