

Seamless Red Brass Pipe Nipple SUBMITTAL DATA SHEET

No-Lead 125LB Threaded Red Brass Pipe Nipples

Red no-lead brass pipe nipples are rated to 125 PSI and can be used in above ground or underground applications. All pipe nipples contain < 0.25% Lead (Pb)

Nipples Available in Lengths from Close to 12"

Schedule 40 diameters from 1/8" to 4"

Red Brass Nipples meets ASTM B43-96 specifications, Meets ASTM B-687 standards

All threads meet ASME/ANSI B1.20.1 standards

Brass steel pipe nipple B43-98		
NPS	OD	WALL THICKNESS
	IN.	IN.
1/8	0.405	0.062
1/4	0.540	0.082
3/8	0.675	0.090
1/2	0.840	0.107
3/4	1.050	0.114
1	1.315	0.126
1-1/4	1.660	0.146
1-1/2	1.900	0.150
2	2.375	0.156
2-1/2	2.875	0.187
3	3.500	0.219
4	4.500	0.250

New Jersey
Distribution Center
500 Green Street
Woodbridge, NJ 07095

Illinois
Distribution Center
2101 Dralle Road
University Park, IL 61727

New Hampshire Distribution
Center
44 Industrial Park Drive
Dover, NH 03820

Ohio
Distribution Center
Central Ohio Ind. Park Bldg. 3
Shelby, OH 44875

Tennessee
Distribution Center
25400 Industrial Park Rd.
Ardmore, TN 38499

Georgia
Distribution Center
4747 Granite Drive
Tucker, GA 30084

N. Carolina
Distribution Center
4742 Highway
Madison, NC 27025

Kansas City
Distribution Center
6530 Winner Road
Kansas City, MO 64125

Texas
Distribution Center
111 E. Lampasas St
Ennis, Texas 75119

California
Distribution Center
1245 N. 5th Street
San Jose, CA 95112