

WIELAND | KESSLER



ISO9001:2015

LF-PP SERIES(LFPMBV1/2P SERIES)

Lead Free Brass Ball Valves PEX * PEX

FEATURES

- Dezincification Resistant (DZR) Lead Free Brass Material
- PEX end Conform To ASTM F1807
- Forged Brass Body
- Blow Out Proof Stem Design
- Packing Nut, O-RING & Packing On The Stem Seal
- Stainless Steel Ball
- Handle With Vinyl Grip

PERFORMANCE RATING

- 600 psi (WOG) 150 psi (WSP) Service
- Temperature Range : -20° F to 300° F



MATERIAL

Part Name	Material
Body	Lead Free Brass
Seat	PTFE
Ball	SS304
Stem O-Ring	NBR
Packing Nut	Brass
Stem	Brass
Lock Nut	Ferrum /Zinc Plated
Lock Washer	Ferrum /Zinc Plated
Packing	PTFE
Handle	Ferrum /Chrome Plated
Cap	Lead Free Brass

DIMENSIONS

Part No.	SIZE	D	L	H	W	Cv	Wt.(lbs.)
LF-PP038	3/8	0.229	3.46	1.64	2.40	2.77	
LF-PP050	1/2	0.354	3.46	1.64	2.44	2.67	0.276
LF-PP075	3/4	0.531	3.46	1.81	2.58	15.02	0.408
LF-PP100	1	0.713	4.29	2.09	3.17	27.01	0.683
LF-PP125	1-1/4	0.874	4.29	2.19	3.62	40.63	
LF-PP150	1 1/2	1.063	5.63	2.36	4.31	60.10	
LF-PP200	2	1.378	5.63	2.62	5.57	101.01	

APPROVALS

IAPMO: ● 3/8"-2" Per NSF/ANSI-61, NSF/ANSI-372 , NSF/ANSI-14

CSA: ● 3/8"-2" Per NSF/ANSI-61, NSF/ANSI-372 ,IGC-157

