



ISO9001:2015

LF-3PP SERIES (LFPRESSBV SERIES)

Lead Free, Full Port Brass Ball Valves PRESS End

FEATURES

- Dezincification Resistant (DZR) Lead Free Brass Material
- PRESS conform ANSI Z1157
- Forged Brass Body
- Blow Out Proof Stem Design
- Packing Nut, O-RING & Packing On The Stem Seal
- Stainless Steel Ball
- Handle With Vinyl Grip

PERFORMANCE RATING

- 250 psi (WOG) 150 psi (WSP) Service
- Temperature Range : -20° F to 300° F



MATERIAL

Part Name	Material
Body	Lead Free Brass
Seat	PTFE
Ball	SS304
Stem O-Ring	NBR
Packing Nut	Brass
Stem	Brass (1/2"-2")
	SS304 (2-1/2"-4")
Lock Nut	Ferrum /Zinc Plated
Lock Washer	Ferrum /Zinc Plated
Packing	PTFE
Handle	Ferrum /Chrome Plated
Cap	Lead Free Brass
Body O-Ring	FKM
Press O-Ring	EPDM

DIMENSIONS

Part No.	SIZE	D	L	H	W	Cv	Wt.(lbs.)
LF-3PP050	1/2	0.591	3.46	1.81	3.15	18.55	0.474
LF-3PP075	3/4	0.748	4.29	2.09	3.60	29.76	0.811
LF-3PP100	1	0.984	4.29	2.25	3.92	51.55	1.146
LF-3PP125	1-1/4	1.259	5.63	2.52	4.41	84.42	1.664
LF-3PP150	1 1/2	1.574	5.63	2.74	5.28	131.93	2.526
LF-3PP200	2	1.949	5.63	3.03	6.79	200.35	3.565
LF-3PP250	2 1/2	2.520	7.76	4.25	7.48	338.43	
LF-3PP300	3	2.894	8.19	4.58	8.19	445.44	
LF-3PP400	4	3.839	9.25	5.49	9.88	783.88	

APPROVALS

IAPMO: ● 1/2"-4" per NSF/ANSI-61, NSF/ANSI-372 ,IGC-157

