

WIELAND | KESSLER



ISO9001:2015

LF-2PP SERIES (LFPROPEXBV SERIES)

Lead Free Brass Ball Valves PROPEX * PROPEX

FEATURES

- Dezincification Resistant (DZR) Lead Free Brass Material
- PROPEX end Conform To ASTM F1960
- Forged Brass Body
- Blow Out Proof Stem Design
- Packing Nut, O-RING & Packing On The Stem Seal
- Stainless Steel Ball
- Handle With Vinyl Grip

PERFORMANCE RATING

- 400 psi (WOG) 150 psi (WSP) Service
- Temperature Range : -20° F to 300° F



MATERIAL

Part Name	Material
Body	Lead Free Brass
Seat	PTFE
Ball	SS304
Stem O-Ring	NBR
Packing Nut	Brass
Stem	Brass
Lock Nut	Ferrum /Zinc Plated
Lock Washer	Ferrum /Zinc Plated
Packing	PTFE
Handle	Ferrum /Chrome Plated
Cap	Lead Free Brass

DIMENSIONS

Part No.	SIZE	D	L	H	W	Cv	Wt.(lbs.)
LF-2PP038	3/8	0.276	3.46	1.64	2.37	4.04	
LF-2PP050	1/2	0.394	3.46	1.69	2.58	8.23	0.328
LF-2PP075	3/4	0.611	3.46	1.81	3.31	19.80	0.483
LF-2PP100	1	0.812	4.29	2.09	3.98	34.98	0.842
LF-2PP125	1-1/4	0.984	4.29	2.25	4.65	51.55	1.250
LF-2PP150	1 1/2	1.103	5.63	2.45	5.52	64.64	1.850
LF-2PP200	2	1.575	5.63	2.74	6.91	131.92	3.117
LF-2PP250	2-1/2	2.010	5.63	3.04	8.80	214.45	
LF-2PP300	3	2.440	7.76	4.25	10.75	316.93	

APPROVALS

IAPMO: ● 3/8"-3" Per NSF/ANSI-61, NSF/ANSI-372, NSF/ANSI-14

